Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	13929	"707"/$.ccls. and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/07/17 20:28
L2	0	"707"/$.ccls. and (@ad<"20010215") and (early near3 flush$3)	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/07/17 20:28
L3	32	"707"/$.ccls. and (@ad<"20010215") and ((early or advan$9 or prior) near3 flush$3)	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/07/17 20:32
L4	19	"707"/$.ccls. and (@ad<"20010215") and (flush$3 with (transaction near3 log))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/07/17 20:32
S1	1	"20020112094"	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/07/12 10:54
S2	371	((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with transaction$3 with log) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 11:01
S3	272	((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log) with (volatil$5 or memory) with (stable or nonvolatil$5 or (non adj volatil$5) or drive or database or disk)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/29 18:48
S4	173	((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log or storage or buffer) with (before or prior) with (end$3 or last) with (transaction$2 or procedure$2 or step$2 or function$2 or directive or message)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 13:16
S5	13	((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log or storage or buffer) with (before or prior) with (end$3 or last) with (transaction$2 or procedure$2 or step$2 or function$2 or directive or message) with (stable or nonvolatil$5 or (non adj volatil$5) or drive or database or disk)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:03
S6	136	(write adj ahead adj log$5) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 09:59

S7	58	(write adj ahead adj log$5) and (@ad<"20010215") and ((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log) with (stable or nonvolatil$5 or (non adj volatil$5) or drive or database or disk))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 09:59
S8	5	((write adj ahead adj log$5) and (@ad<"20010215")) and (((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log or storage or buffer) with (before or prior) with (end$3 or last) with (transaction$2 or procedure$2 or step$2 or function$2 or directive or message)) and (@ad<"20010215"))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:24
S9	55	(implicit adj transaction) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:04
S10	14	(fallback with module) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:05
S11	11	"4507751".pn. or "5261089".pn. or "5751962".pn. or "5841972". pn. or "5864842".pn. or "5884299".pn. or "5922072".pn. or "5933601".pn. or "5960181". pn. or "5961642".pn. or "5978576".pn.	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:08
S12	3	("4507751".pn. or "5261089".pn. or "5751962".pn. or "5841972". pn. or "5864842".pn. or "5884299".pn. or "5922072".pn. or "5933601".pn. or "5960181". pn. or "5961642".pn. or "5978576".pn.) and ((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:08
S13	26	(parallel$5 with process$3) and ((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log or storage or buffer) with (before or prior) with (end$3 or last) with (transaction$2 or procedure$2 or step$2 or function$2 or directive or message)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 10:27

S14	1	"20020112094" and (write adj ahead adj log$5)	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 20:15
S15	1	"20020112094" and ((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log) with (volatil$5 or memor or stable or nonvolatil$5 or (non adj volatil$5) or drive or database or disk))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/03/30 20:16
S16	333	((flush$3 or writ$3) with transaction with (synchron$9 or concurren$9)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/07/12 09:13
S17	25	((flush$3 or writ$3) with transaction with log with (synchron$9 or concurren$9)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/07/12 10:53
S18	27	((flush$3 or writ$3 or transfer$5) with transaction with log with (synchron$9 or concurren$9)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2004/07/12 10:54
S20	3347	((flush$3 or writ$3 or mov$3 or transfer$5) same (transaction$3 or log) same (before or prior or first advan$9) same (end or last or commit$5)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 14:47
S21	515	((flush$3 or writ$3 or mov$3 or transfer$5) same (transaction$3 or log) same (before or prior or first advan$9) same (end or last) with (procedure or operation or step)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 13:04
S22	333	(((flush$3 or writ$3 or mov$3 or transfer$5) with (transaction$3 or log)) same (before or prior or first advan$9) same ((end or last) with (procedure or operation or step))) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 14:50
S23	212	(transaction or log).ab. and (((flush$3 or writ$3 or mov$3 or transfer$5) with (transaction$3 or log)) same (before or prior or first advan$9) same ((end or last) with (procedure or operation or step))) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 20:07

S24	1285	((flush$3 or writ$3 or mov$3 or transfer$5) same (transaction$3 or log) same (before or prior or first advan$9) same (end or last or commit$5)) and (@ad<"20010215") and (fallback$5 or (fall adj back) or mirror or replica$7 or backup or duplicat$5)	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 14:48
S25	10	(((flush$3 or writ$3 or mov$3 or transfer$5) with (transaction$3 or log)) same (before or prior or first advan$9) same ((end or last) with statement)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 20:01
S26	396	(transaction or log).ab. and ((flush$3 or writ$3 or mov$3 or transfer$5) with (transaction$3 or log) with (before or prior or first or advanc$9) with (end or last or commit)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 20:09
S27	1	(transaction or log).ab. and ((flush$3 or writ$3 or mov$3 or transfer$5) with (transaction$3 or log) with (before or prior or first or advanc$9) with (end or last or commit)) and (@ad<"20010215") and (fallback$5 or (fall adj back))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/02/04 20:10
S28	135	(transaction or log).ab. and ((flush$3 or writ$3 or mov$3 or transfer$5) with (transaction$3 or log) with (before or prior or first or advanc$9) with (end or last or commit)) and (@ad<"20010215") and (fallback$5 or (fall adj back) or mirror or replica$7 or backup or duplicat$5)	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 12:08
S30	3	"6321234".pn. "6684223".pn. "5006978".pn.	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 12:42
S31	3	("6321234".pn. "6684223".pn. "5006978".pn.) and ((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 12:43
S32	2	("6321234".pn. "6684223".pn. "5006978".pn.) and ((flush$3 or delet$3 or clear$3 or remov$3 or mov$3 or transfer$5) with (transaction$3 or log) with (earl$5 or before or prior or ahead or first))	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 12:44

S33	0	(teradata same ((write adj ahead adj log$5) or wal)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 13:17
S34	140	teradata and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/07/17 20:27
S35	0	(teradata same ((write adj ahead adj log$5) or wal)) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 13:17
S36	1	teradata and ((write adj ahead adj log$5) or wal) and (@ad<"20010215")	US-PGPUB; USPAT; IBM_TDB	OR	ON	2005/06/29 13:17